

DECLARATION OF PERFORMANCE

According to ANNEX III of the regulation (EU) N° 305/2011

Nullifire
Smart Protection

No. FS703 – 20160224

- 1. Unique identification code of the product-type:** FS703
- 2. Intended use/es:** A fire resistant, one part silicone based sealant used to form linear gap seals where gaps are present in wall and floor constructions.
- 3. Manufacturer:** tremco illbruck Limited, Coupland Road, Hindley Green, Wigan, UK. WN2 4HT
- 5. System/s of AVCP:** System 1
- 6. European Assessment Document:** ETAG 026 edition 2011 used as EAD
European Technical Assessment: ETA 14/0449 of 07/01/2015
Technical Assessment Body: Warrington Certification Limited
Notified Body: 1121, Warrington Certification Limited
- 7. Declared performance/s:**

Essential Characteristic	Performance	Harmonised Technical Specification
Safety in Case of Fire		
Reaction to fire	Class F	EN13501-1
Resistance to fire	Up to EI240 Resistance to fire performance, in accordance with EN13501-2 See ETA 14/0449 clause 3.2 - Annex C	EN13501-2 EN1366-4: 2006
Hygiene, Health and Environment		
Dangerous Substances	Does not contain dangerous substances See ETA 14/0449 Clause 3.5	
Air Permeability	Test Pressure Differential 600 Pa See ETA 14/0449 Clause 3.4	EN 1026
Energy, Economy and Heat Retention		
Service & Durability	X intended for use in conditions exposed to weathering in accordance with EOTA Technical Report TR024 – Edition November 2006	ETAG 026-3

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:
M. Liptrot, Business Unit Director Sealants & Coatings
At Wigan on 24 February 2016



Annex:

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according Regulation (EU) No. 1907/2006 (REACH), Annex II is available on the website to support this Declaration of Performance.

DECLARATION OF PERFORMANCE

According to ANNEX III of the regulation (EU) N° 305/2011

Nullifire
Smart Protection

No. FS703 – 20160224

CE	
tremco illbruck Limited, Coupland Road, Hindley Green, Wigan. WN2 4HT UK 14 1121-CPR-JA5052 FS703 – 20160122 www.nullifire.com/FS703/	
EN 1366-4: 2006 ETA 14-0449 ETAG 26, Part 3 A fire resistant, one part silicone based sealant used to form linear gap seals where gaps are present in wall and floor constructions.	
Essential Characteristic	Performance
Safety in Case of Fire	
Reaction to fire	Class F
Resistance to fire	Up to EI240 Resistance to fire performance, in accordance with EN13501-2 See ETA 14/0449 clause 3.2 - Annex C
Hygiene, Health and Environment	
Dangerous Substances	Does not contain dangerous substances See ETA 14/0449 Clause 3.5
Air Permeability	Test Pressure Differential 600 Pa See ETA 14/0449 Clause 3.4
Energy, Economy and Heat Retention	
Service & Durability	X intended for use in conditions exposed to weathering in accordance with EOTA Technical Report TR024 – Edition November 2006
Other	NPD