

GU aluminium cleaner



Product description

GU aluminium cleaner removes dust, adhesive residues from protective films, marking pencil, traces of rubber, fresh PUR foam and fresh sealing compound residue, and tar and bitumen spatters. GU aluminium cleaner is used to clean adhesion surfaces prior to gluing, and for removing residues of various adhesive systems prior to curing.

Applications

- GU aluminium cleaner is used in trade and industry as a low-odour, fast-drying specialised cleaner
- Owing to its good compatibility with many coated surfaces it is perfectly suited to many areas of plastics and metals processing
- GU aluminium cleaner is used by specialist companies on powder-coated and anodised aluminium profiles and PUR profiles



Technical data and requirements

GU aluminium cleaner	Classification and grading	NF / ISO / DIN standard
Base	mixed aliphatic hydrocarbons, free of aromatics and chlorinated hydrocarbons	
Density [1]	approx.. 0.71 g/cm ³	DIN EN 542
Minimum processing temperature	from +5 °C	
Flash point	-14 °C	
Ignition temperature	+260 °C	

[1] Measured at 20 °C.

Order information

Description	Packing	Contents	Colour	PU/Box*	Order number
GU aluminium cleaner	Metal bottle	1,000 ml	–	12 pcs	H-00014-00-0-0

* Other container sizes available on request.

Order information – Accessories

Description	PU	Order number
GU water-saving moistener, empty, filling volume max. 4 litres	1 pc	H-01177-00-0-0

Processing

- The dry, dust-free surface of the material is cleaned using a dry, lint-free and non-staining cloths made of cellulose or cotton.
- In general, GU aluminium cleaner does not dissolve or etch coated surfaces; however, because of the variety of surfaces and coating formulations in use, we recommend carrying out suitability tests.
- If coloured pigments can be seen in the cleaning cloth when cleaning powder-coated surfaces, this may be an indication that the powder coating is not sufficiently cured. In this case, the powder coating company should also be contacted at the same time.

Storage

- Original container tightly sealed, dry at temperatures of +15 °C to +25 °C out of direct sunlight.

